

IN THE CLAIMS:

Please amend Claims 1 to 6, 9, 14 and 18 to 21, as follows.

---

1. (Currently Amended) An image pickup apparatus comprising:  
first and second image pickup portions for receiving at least a first  
wavelength component of an object light and a second wavelength component of the object  
light different from the said first wavelength component, respectively;

first and second optical systems for projecting the object light onto said first  
and second image pickup portions, respectively, via different optical paths, said second  
optical system projecting the object light also onto said first image pickup portion portions;  
and

guide a guide path forming portions arranged correspondingly with said first  
and second image pickup portions, respectively, so that each of said guide path forming  
portions receives the object light including the first and second wavelength components  
and provides different guide paths thereto, respectively, so as to guide the wavelength  
component from the optical system corresponding to each of said guide path forming  
portions among the received first and second wavelength components onto the image  
pickup portion corresponding to each of said guide path forming portions portion for  
forming a guide path for receiving the object light projected by said first optical system and  
guiding the received object light to said first image pickup portion, said guide path forming  
portion receiving the object light projected by said second optical system onto said first  
image pickup portion and not guiding the received object light to said first image pickup  
portion.

2. (Currently Amended) An image pickup apparatus according to  
claim 1, wherein the said first wavelength component is a representative wavelength of

light of a first spectral distribution and the said second wavelength component is a representative wavelength of light of a second spectral distribution which is different from the said first spectral distribution.

3. (Currently Amended) An image pickup apparatus according to claim 2, wherein the said first spectral distribution is a spectral distribution including a peak wavelength of a luminosity factor.

4. (Currently Amended) An image pickup apparatus according to claim 1, wherein the said first wavelength component is included in a spectral distribution including a peak wavelength of a luminosity factor.

5. (Currently Amended) An image pickup apparatus according to claim 1, wherein the said first and second wavelength components are two different color components among red, green, and blue.

6. (Currently Amended) An image pickup apparatus according to claim 1, wherein said first and second optical systems comprise a filter for extracting said first and second wavelength components, ~~components~~ respectively.

7. (Original) An image pickup apparatus according to claim 1, wherein each of said first and second optical systems comprises a single lens.

8. (Original) An image pickup apparatus according to claim 7, wherein said single lenses of said first and second optical systems are integrally formed of a glass material or a resin material.

9. (Currently Amended) An image pickup apparatus according to claim 8, ~~claim 8~~ further comprising:

a light shielding layer provided between said integrally formed single lenses.

10. (Original) An image pickup apparatus according to claim 1, wherein each of said first and second optical systems comprises a single lens provided with an infrared radiation cutting filter.

*Al and*  
11. (Original) An image pickup apparatus according to claim 1, wherein each of said first and second optical systems comprises photochromic glass.

12. (Original) An image pickup apparatus according to claim 1, wherein each of said first and second optical systems comprises a color purity correction filter.

13. (Original) An image pickup apparatus according to claim 1, wherein each of said first and second optical systems comprises a filter whose transmission factor becomes smaller as the distance from an optical axis thereof becomes longer.

14. (Currently Amended) An image pickup apparatus according to claim 1, wherein, when a virtual object distance  $D$  [m] is defined as a function of an image pickup angle  $\theta$  [°] of said first or second optical systems to be  $D = 1.4 / \tan (\theta/2)$ , an interval between optical axes of said first and second optical systems is set such that change in an interval between an object image of the said first wavelength component received by said first image pickup portion and an object image of the said second wavelength component received by said second image pickup portion between when an

object is at the said virtual distance and when the object is at infinity is smaller than a pixel pitch of said image pickup portions multiplied by two.

15. (Original) An image pickup apparatus according to claim 1, wherein said first and second image pickup portions are integrally formed.

16. (Original) An image pickup apparatus according to claim 1, wherein said first and second image pickup portions are formed in a plane shape.

*Alt*  
17. (Original) An image pickup apparatus according to claim 1, further comprising:

a plurality of openings for taking in external light through said first and second optical systems.

18. (Currently Amended) An image pickup apparatus according to claim 1, wherein said guide path forming portions comprise ~~portion comprises~~ a first filter for extracting the said first wavelength component and a second filter for extracting the said first wavelength component which comes through said first filter.

19. (Currently Amended) An image pickup apparatus according to claim 1, wherein each of said guide path forming portions ~~portion~~ comprises a first polarizing filter for transmitting the object light received by said first image pickup portion and a second polarizing filter of a same polarizing direction as that of said first polarizing filter for transmitting the object light which comes through said first polarizing filter.

20. (Currently Amended) An image pickup apparatus according to claim 1, wherein said guide path forming portions include ~~portion includes~~ a microlens for receiving the object light projected by said first optical system and guiding the object light to said first image pickup portion, said microlens receiving the object light projected by said second optical system onto said first image pickup portion and not guiding the object light to said first image pickup portion.

*Amel*

21. (Currently Amended) An image pickup apparatus according to claim 1, wherein said guide path forming portions include ~~portion includes~~ a micro lens for receiving the object light projected by said first optical system and guiding the object light to said first image pickup portion, said microlens being offset so as to receive the object light projected by said second optical system onto said second ~~first~~ image pickup portion and not to guide the object light to said first image pickup portion.

---